



EnergyCell Front Terminal Battery

VRLA Battery for Renewable Energy Storage

- Front terminal access design for ease of maintenance and installation
- High-density pasted plates for high cycle life
- Lead-calcium-tin alloy plates for long life in both cycling and float applications
- High recharge efficiency
- Compact footprint for higher energy density requirements
- Thermally welded case-to-cover bond to eliminate leakage
- UL-recognized component



The EnergyCell RE valve regulated lead acid battery is designed for high power density and renewable energy cycling applications. Absorbed Glass Matt (AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance. The EnergyCell RE also features low profile terminals with threaded copper alloy inserts providing reduced maintenance and increased safety.

OutBack
POWER™
member of The  Group™

www.outbackpower.com

EnergyCell Front Terminal Battery

	EnergyCell 170RE	EnergyCell 200RE
Cells Per Unit	6	6
Voltage Per Unit	12 Vdc	12 Vdc
Operating Temperature Range (with temperature compensation)	Discharge: -40°F (-40°C) to +160°F (71°C) Charge: -10°F (-23°C) to +140°F (60°C)	
Optimal Operating Temperature Range	+74°F (23°C) to +80°F (27°C)	
Recommended Maximum Charging Current Limit Per String	25 Adc	30 Adc
Float Charging Voltage	13.62 to 13.8 Vdc / unit average at 77°F (25°C)	
Equalization and Cycle Service Charging Limits	14.4 to 14.8 Vdc / unit average at 77°F (25°C)	
Self Discharge	Battery can be stored up to 6 months at 77°F (25°C) before a freshening charge is required. Batteries stored at temperatures greater than 77°F (25°C) will require recharge sooner than batteries stored at lower temperatures.	
Temperature Compensation Factor (Charging)	5mV per degree C per cell (2V)	
Terminal	Threaded copper alloy insert terminal to accept ¼-20 UNC bolt	
Terminal Hardware Initial Torque	110 in-lbs (12.4 Nm)	
Weight (lbs. / kg)	115 lbs (52 kg)	131 lbs (60kg)
Dimensions H x D x W (in / cm)*	11.14 x 22.01 x 4.95" (28.3 x 55.9 x 12.6 cm)	12.60 x 22.01 x 4.95" (32.0 x 55.09 x 12.6 cm)

*Batteries to be installed with 0.5" (12.7 mm) spacing minimum and free air ventilation

Ampere Hour Capacity to 1.75 Volts Per Cell @ 77°F (25°C)

Discharge in Hours	EnergyCell 170RE	EnergyCell 200RE
1	89.1	103.0
3	114.2	132.0
4	120.6	139.6
5	125.9	145.5
8	137.0	158.4
12	145.3	168.0
20	153.8	178.0
24	157.0	181.4
48	163.9	189.6
100	170.0	200.0

Specifications subject to change without notice

For contact information visit www.outbackpower.com



Main Office:

5917 195th St. NE #7
 Arlington, WA 98223 USA
 Phone: (360) 435.6030
 Fax: (360) 435.6019

www.outbackpower.com

