



FX & VFX Series

Sealed & Vented True Sinewave Inverter/Charger

Sealed FX

- Sinewave Output
- Intelligent Battery Charging
- Modular, Stackable Design
- High Operating Efficiency
- Weather-resistant Sealed Chassis
- Corrosion Resistant Internal Components
- Field Serviceable
- Integrated Network Communications
- Standard 5-Year Warranty

Vented VFX

- Sinewave Output
- Intelligent Battery Charging
- Modular, Stackable Design
- High Operating Efficiency
- Bug Proof Chassis
- Corrosion Resistant Internal Components
- Field Serviceable
- Integrated Network Communications
- Standard 5-Year Warranty



Vented VFX

Sealed FX



OutBack Power's true sinewave inverter/charger is a complete power solution. It incorporates a DC-to-AC sinewave inverter, battery charger and AC transfer relay housed within a die-cast aluminum chassis. Intelligent multistage battery charging reduces generator run-time and prolongs the life of your batteries. Built-in networked communications enables multiple units to be stacked and connected with other OutBack Power electronics providing industry leading integration and near infinite application flexibility. The exclusive modular system architecture means that increased power output is just an additional inverter/charger away.

Our flagship FX series uses a sealed chassis that can operate in the harshest environmental conditions such as high humidity and corrosive salt air. The VFX series uses a vented chassis with bug proof screened openings that allow high output AC power in the hottest of operating conditions.

OutBack Power Inverter/Chargers are the only choice when you need a true sinewave, powerful, modular and reliable power solution for your home, business or extreme application.

OutBack
POWER™
member of The **alphan** Group™

www.outbackpower.com

FX & VFX Series Specifications

| | | Sealed Models | | | Vented Models | | |
|---|-------------------|---|-----------------|-----------------|---|-----------------|-----------------|
| | | FX2012T | FX2524T | FX3048T | VFX2812 | VFX3524 | VFX3648 |
| Nominal DC Input Voltage | | 12 VDC | 24 VDC | 48 VDC | 12 VDC | 24 VDC | 48 VDC |
| Continuous Power Rating at 25°C (77°F) | | 2000 VA | 2500 VA | 3000 VA | 2800 VA | 3500 VA | 3600 VA |
| AC Voltage/Frequency | | 120 VAC / 60 Hz | 120 VAC / 60 Hz | 120 VAC / 60 Hz | 120 VAC / 60 Hz | 120 VAC / 60 Hz | 120 VAC / 60 Hz |
| Continuous AC RMS Output at 25°C (77°F) | | 17 Amps AC | 20.8 Amps AC | 25 Amps AC | 23.3 Amps AC | 29.2 Amps AC | 30 Amps AC |
| Idle Power | Full | ~ 20 Watts | ~ 23 Watts | ~ 23 Watts | ~ 20 Watts | ~ 20 Watts | ~ 23 Watts |
| | Search | ~ 6 Watts | ~ 6 Watts | ~ 6 Watts | ~ 6 Watts | ~ 6 Watts | ~ 6 Watts |
| Typical Efficiency | | 90% | 93% | 93% | 90% | 92% | 93% |
| Total Harmonic Distortion | Typical | 2% | 2% | 2% | 2% | 2% | 2% |
| | Maximum | 5% | 5% | 5% | 5% | 5% | 5% |
| Output Voltage Regulation | | ±2% | ±2% | ±2% | ±2% | ±2% | ±2% |
| Maximum Output Current | Peak | 56 Amps AC | 70 Amps AC | 70 Amps AC | 56 Amps AC | 70 Amps AC | 70 Amps AC |
| | RMS | 40 Amps AC | 50 Amps AC | 50 Amps AC | 40 Amps AC | 50 Amps AC | 50 Amps AC |
| AC Overload Capability | Surge | 4800 VA | 6000 VA | 6000 VA | 4800 VA | 6000 VA | 6000 VA |
| | 5 Seconds | 4000 VA | 4800 VA | 4800 VA | 4000 VA | 5000 VA | 5000 VA |
| | 30 Minutes | 2500 VA | 3200 VA | 3200 VA | 3200 VA | 4000 VA | 4000 VA |
| AC Input Current Maximum | | 60 Amps AC | 60 Amps AC | 60 Amps AC | 60 Amps AC | 60 Amps AC | 60 Amps AC |
| AC Input Voltage Range (MATE Adjustable) | | 80 to 150 VAC | 80 to 150 VAC | 80 to 150 VAC | 80 to 150 VAC | 80 to 150 VAC | 80 to 150 VAC |
| AC Input Frequency Range | | 55 to 65 Hz | 55 to 65 Hz | 55 to 65 Hz | 55 to 65 Hz | 55 to 65 Hz | 55 to 65 Hz |
| DC Input Voltage Range | | 10.5 to 17 VDC | 21 to 34 VDC | 42 to 68 VDC | 10.5 to 17 VDC | 21 to 34 VDC | 42 to 68 VDC |
| Continuous Battery Charger Output | | 80 Amps DC | 55 Amps DC | 35 Amps DC | 125 Amps DC | 82 Amps DC | 45 Amps DC |
| Temperature Range | Rated | 0 to 50°C (power derated above 25°C) | | | 0 to 50°C (power derated above 25°C) | | |
| | Maximum | -25 to 60°C (Functions, but does not necessarily meet all component specifications) | | | -25 to 60°C (Functions, but does not necessarily meet all component specifications) | | |
| Certifications | | ETL Listed to UL1741 | | | ETL Listed to UL1741 | | |
| Warranty | | Standard 5 year Warranty | | | Standard 5 year Warranty | | |
| Weight | Unit | 62 lbs (29 kg) | | | 61 lbs (28 kg) | | |
| | Shipping | 67 lbs (30 kg) | | | 67 lbs (30 kg) | | |
| Dimensions (H x W x L) | Unit | 13 x 8.25 x 16.25" (33 x 21 x 41 cm) | | | 12 x 8.25 x 16.25" (30 x 21 x 41 cm) | | |
| | Shipping | 21.75 x 13 x 22" (55 x 33 x 56 cm) | | | 21.75 x 13 x 22" (55 x 33 x 56 cm) | | |

Available From:



Blue Pacific Solar™
www.BluePacificSolar.com



Corporate Office:
17825 59th Ave. NE, Suite B
Arlington, WA 98223 USA
Phone: +1 360 435 6030
Fax: +1 360 435 6019

European Office:
Hansastrasse 8
D-91126
Schwabach, Germany
Phone: +49 9122 79889 0
Fax: +49 9122 79889 21

Asia Office:
Suite 1903, Tower 1, China Hong Kong City
33 Canton Road, Kowloon
Hong Kong
Phone: +852 2736 8663
Fax: +852 2199 7988

Latin American Office:
15105 Cedar Bluff Pl.
Wellington, FL 33414 USA
Phone: +1 561 792 9651
Fax: +1 561 792 7157